

Metalux

UHBS2

Lumen and CCT Select
LED Round High Bay

Setting a new standard in Selectable High Bays!

The UHBS2 signature round form factor is perfect for new installs and retrofit opportunities. Offered in three compact sizes, with selectable lumens, 5 CCT select, and field selectable distribution, the UHBS2 replaces 135 possible configurations with just 3 fixtures! With NSF Certification, IP65 and NEMA 4X rating, the UHBS2 is suitable for almost any type of environment.



Scan for more.



Easy

Sensor ready port for quick plug and play install. EasyMount design provides quicker installation time.



Versatility

Field selectable distribution – Narrow, Medium, or Wide. Selectable Lumen/Power and 5 color Selectable CCT.



Durability

Diecast aluminum housing and heatsink. Polycarbonate lens seals LED for IP65 rating and IK10 impact protection.

Industrial • Commercial • Retail • Manufacturing • Warehouse • Gymnasium
• Multi-purpose • Grocery • High Bay / Low Bay Applications



COOPER
Lighting Solutions

a **signify** business



Powered by Crescent™

*All items not stocked in all locations. Due to the franchise restrictions, all items may not be available at every location and may be substituted where appropriate. We reserve the right to limit quantities and correct typographical errors.

crescentelectric.com

Energy and Performance Data

Default CCT / Lumen / Distribution Setting: 4000K / High Power / Wide

Catalog#	UPC	Voltage	Lumen Setting	Nominal CCT	Nominal Lumens			Wattage (120V)	Efficacy (lm/W)		
					Narrow	Medium	Wide		Narrow	Medium	Wide
UHBS2-1218-MV-L8C5-U	080083301836	120-347V	Low	3000K	11304	11445	12267	80.2	140.9	142.7	153.0
				3500K	11583	11728	12571	79.4	145.9	147.7	158.3
				4000K	11761	11908	12764	78.6	149.6	151.5	162.4
				5000K	11868	12016	12880	79	150.2	152.1	163.0
				6500K	11809	11956	12816	80.4	146.9	148.7	159.4
			Medium	3000K	13629	13799	14791	98.9	137.8	139.5	149.6
				3500K	13986	14160	15178	97.6	143.3	145.1	155.5
				4000K	14280	14459	15498	96.5	148.0	149.8	160.6
				5000K	14265	14443	15481	96.6	147.7	149.5	160.3
				6500K	14092	14268	15293	98.7	142.8	144.6	154.9
			High	3000K	16256	16459	17642	122	133.2	134.9	144.6
				3500K	16800	17009	18232	120.5	139.4	141.2	151.3
				4000K	17145	17359	18607	119.1	144.0	145.8	156.2
				5000K	17296	17511	18770	119.2	145.1	146.9	157.5
				6500K	17002	17214	18451	122.1	139.2	141.0	151.1
UHBS2-2436-MV-L8C5-U	080083301843	120-347V	Low	3000K	23839	24137	25872	156	152.8	154.7	165.8
				3500K	24695	25003	26801	154.4	159.9	161.9	173.6
				4000K	25223	25538	27374	152.8	165.1	167.1	179.1
				5000K	25575	25895	27756	153.7	166.4	168.5	180.6
				6500K	25324	25640	27483	154.2	164.2	166.3	178.2
			Medium	3000K	29445	29813	31956	194.6	151.3	153.2	164.2
				3500K	30244	30621	32823	192.4	157.2	159.2	170.6
				4000K	30998	31385	33641	190	163.1	165.2	177.1
				5000K	30989	31376	33632	191	162.2	164.3	176.1
				6500K	30334	30713	32921	195	155.6	157.5	168.8
			High	3000K	34846	35281	37818	239.4	145.6	147.4	158.0
				3500K	35898	36346	38959	235.5	152.4	154.3	165.4
				4000K	36613	37070	39735	232.1	157.7	159.7	171.2
				5000K	36861	37321	40005	233.5	157.9	159.8	171.3
				6500K	36207	36659	39295	239.1	151.4	153.3	164.3
UHBS2-4860-MV-L8C5-U	080083301850	120-347V	Low	3000K	45254	46252	48002	317.7	142.4	145.6	151.1
				3500K	46918	47952	49767	312.7	150.0	153.3	159.2
				4000K	48093	49153	51014	308.9	155.7	159.1	165.1
				5000K	48590	49661	51541	310.6	156.4	159.9	165.9
				6500K	47645	48696	50539	316.5	150.5	153.9	159.7
			Medium	3000K	49744	50841	52765	356.0	139.7	142.8	148.2
				3500K	51573	52710	54705	350.5	147.1	150.4	156.1
				4000K	52865	54031	56076	346.2	152.7	156.1	162.0
				5000K	53411	54589	56655	348.1	153.4	156.8	162.8
				6500K	52373	53528	55554	354.7	147.7	150.9	156.6
			High	3000K	53388	54565	56630	387.9	137.6	140.7	146.0
				3500K	55350	56571	58712	381.8	145.0	148.2	153.8
				4000K	56737	57988	60183	377.2	150.4	153.7	159.6
				5000K	57323	58587	60805	379.2	151.2	154.5	160.4
				6500K	56209	57448	59623	386.5	145.4	148.6	154.3



	Features	Benefits	Result
Construction	Field adjustable distribution provides Narrow, Medium, or Wide	Delivers multiple applications flexibility	↕
	Sensor ready port for quick plug and play install	Increased energy savings and faster ROI	✋ ↕
	Accessible driver allows for custom wiring and optional MWS	Easy install	✋ ↕
Performance	5 CCT and Lumen selectable options available	Reduces sku complexity and inventory cost	✋ ↕
	Up to 60,000 lumen and 180 LPW	Replace 1000W with 239W for significant energy savings	✋
	Product is NEMA 4X, IP65 and NSF rated	Meets project requirements	✋ ↕ ✓
	Full commercial offering and 5-year limited warranty	Guaranteed quality	✓

Product Certifications and Features

