

CYL Wall Cylinder

LUMARK AP

The Lumark AP CYL Wall Cylinder is a high-performance, energy-efficient wall sconce designed for both indoor and outdoor applications. Featuring customizable CCT and wattage selectability, it provides superior light distribution and durability. Its robust construction ensures long-lasting performance, making it an ideal, low-maintenance solution for any lighting project.

Target **AUDIENCE**

Electrical Contractors, Distributors, Facility Managers, Specifiers


Target **APPLICATIONS**

Parking lots, walkways, building areas, stairways
entryways, facades, and awnings



CYL Wall Cylinder

- Selectable CCT (3000-4000-5000K) and wattage (15-20-30-36W) options
- Selectable light distribution (Downlight/Uplight/Both)
- Up to 3,600 lumens
- Efficacies up to 120 lumens per watt
- Energy and maintenance savings up to 57%
- Heat-resistant polycarbonate lens located under impact-resistant tempered glass



SCAN FOR MORE

Cooper Lighting Solutions
CYL Wall Cylinder



Competitor A

Competitor B

LED SYSTEM			
Selectable CCT	✓	✓	✓
Standard CRI	80	90	80
TM-21 @ 50K hrs	89%	Not Listed	70%
LUMENS/EFFICACY			
Selectable Lumens	✓	✓	X
Max Lumens	3,600	3,300	4,520
CCT Selectable Options	3	3 & 5	X
Wattage Selectable Options	4	3	X
Max HID Wattage Replacement	70W	Not Listed	Not Listed
Voltage	120-347V	120-277V	120-347V
Efficacy	up to 120 LPW	95 LPW	up to 153 LPW
DISTRIBUTIONS			
Selectable Light Direction	Up/Down/Up + Down	Up/Down/Up + Down	Up/Down/Up + Down
Beam Angle	50°	25°/40°/60°	45°/75°
OPTIONS			
Photocontrol	✓	✓	✓
Interchangeable Mounting Hardware	X	✓	X
LISTINGS/RATINGS			
DLC Premium	✓	X	X
Ambient Environment	-40°C to 40°C	-40°C to 50°C	-40°C to 40°C
IP Rating	IP65	IP65	X

To learn more about Lumark products, please visit www.cooperlighting.com/global/brands/lumarkap