

Product data sheet

Characteristics

SSP03XDSE20A

Surge protection device, XDSE, 200kA,
240/120 VAC HLD, 3 phase, 4 wire, SPD type
2



Main

Product	Surge protection device
---------	-------------------------

Complementary

Surge Current	200 A per phase
Voltage Rating	240/120 V HLD AC
Number of Phases	3 phase
Wiring Configuration	4-wire
MCOV	150 V 320 V
Rated Current	20 kA
Input voltage	700 V L-N 1200 V L-N 700 V L - G 1200 V L - G 600 V L - L 1000 V N - G 2000 V N - G
Height	5.98 in (152 mm)
Width	5.98 in (152 mm)
Depth	3.98 in (101 mm)

Environment

Enclosure Rating	NEMA 4X
------------------	---------

Ordering and shipping details

Category	08466-SURGE PROTECTION HWA
Discount Schedule	DE1B
GTIN	3606486149188
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.70 in (14.478 cm)
Package 1 Width	10.70 in (27.178 cm)
Package 1 Length	12.80 in (32.512 cm)
Package 1 Weight	3.98 lb(US) (1.805 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes