

Product data sheet

Characteristics

8903SPF12V02

Contactor, Type S, multipole lighting,
mechanically held, 60A, 4 pole, 110/120 VAC
50/60 Hz coil, NEMA 1 flush



Main

Product	Mechanically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	60 A
Number of Poles	4P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical Connection	Lugs
Height	15.20 in (386 mm)
Depth	5.43 in (138 mm)
Width	8.94 in (227 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel flush none
Product certifications	UL Listed CSA

Ordering and shipping details

Category	21324 - 8903 S (NOT S*C) MECH.
Discount Schedule	CP1
GTIN	NULL
Nbr. of units in pkg.	1
Package weight(Lbs)	23.20 lb(US) (10.523 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	15.20 in (38.6 cm)
Package 1 width	8.94 in (22.7 cm)
Package 1 Length	5.43 in (13.8 cm)

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------