



Main

Product	End Closure
Range	I-Line

Complementary

Rated Operational Voltage	600 V AC/DC 50/60 Hz
Length	16.72 in (424.69 mm)
Height	7.06 in (179.32 mm)
Width	1 in (25.40 mm)
For Use with	Busbar trunking 2500 A aluminium end caps Busbar trunking 3200 A copper end caps

Environment

Standards	UL 857 CSA C22.2 No 27:1994 IEC 61439-6
-----------	---

Ordering and shipping details

Category	20199-WALL FLANGES/END CLOSURES
Discount Schedule	PE8
GTIN	785901816201
Nbr. of units in pkg.	1
Package weight(Lbs)	10.63 lb(US) (4.822 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.00 in (15.24 cm)
Package 1 width	11.00 in (27.94 cm)
Package 1 Length	20.00 in (50.8 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------